

# Flooring Film

## Datasheet

### Specifications

### Flooring Film

<b>Product name:</b>	Flooring Film
<b>Media:</b>	Anti-slip PVC
<b>Production description:</b>	Flooring Film is 180mic. anti-slip matte PVC film with acrylic pressure sensitive adhesive. Applied on laminating floor image against slip and damage while stepping on it.
<b>Features:</b>	Flooring Film is a thick PVC film with chemical process to make the surface rough and slip-resistant. Excellent Adhesive on graphic media. The film renders good protection against moisture and is washed with water easily.
<b>Vinyl specification:</b>	<ul style="list-style-type: none"><li>● composition: monomeric calendered PVC</li><li>● thickness of vinyl: 180micron.</li><li>● Weight: 265gsm</li><li>● surface: matte slip-resistant</li></ul>
<b>Release liner</b>	<ul style="list-style-type: none"><li>● 100gsm</li><li>● release strength: 15g/inch</li></ul>
<b>Solvent acrylic pressure sensitive gelatin</b>	<ul style="list-style-type: none"><li>● Adhesive: permanent</li><li>● glue thickness : 25 mic.</li></ul>
<b>Standard size:</b>	50"(1.27m) x 150" (46m)
<b>Shelf life:</b>	12 months
<b>Packing:</b>	1roll/CTN, 3" (76mm) core.
<b>Shrinkage:</b>	shrink in 1% without printed ink at outdoor for one year.
<b>Storage condition:</b>	<ul style="list-style-type: none"><li>● Keep all finished rolls on horizontal position, avoid from direct sun light.</li><li>● Recommend storage between temperature 15<sup>o</sup> - 25<sup>o</sup>C (59<sup>o</sup> - 77<sup>o</sup>F) and 35-65% relative humidity.</li></ul>

Above all information are true and genuine from lab experiment, however this company is not liable to any claim or compensation these data incurred.